

# CE APPROVAL CERTIFICATE

Issued by : TUV NEL Ltd.

EC Notified Body No. 0320

Project No. PPE800000

NEL I.D.

Certificate No. BSEN795/08/009

Date of Issue 18 May 2008



NEL  
East Kilbride, Glasgow,  
G75 0QF, UK.

Tel No. 01355 220222  
Fax No. 01355 272999

**Customer** Kee Safety Ltd.

**Customer address** Unit A2 Cradley Business Park, Overend Road, Cradley Heath, West Midlands, B64 7DW, UK.

**Project No.** PPE800000 **NEL Test Mark** MMMX-11 & 12

**Product Received** 26 July 1994 **Product Tested** 26 July 1994

**Product** Class A1 Structural Anchor

**Model** M12 threaded shank eyebolts supplied in 3 shank lengths i.e. 100, 152 and 204 mm and manufactured in hot galvanised steel or stainless steel. These eyebolts are specifically designed as Class A1 EN795 anchorage device for use only on brick, stone or concrete.

**Parameters** See 'Appendix 1 – Eyebolt Codes and Reference Numbers' overleaf.

**Category of PPE** III

**Method of Test** Tests were carried out to the appropriate clauses of BSEN795 : 1994.

**Remarks** The above mentioned product fulfils the essential health and safety requirements of directive 89/686/EEC and its amendments.

**Distribution**  
Kee Safety Ltd: 1 Copy  
NEL : 2 Copies

Approved By D. Hare.....

Checked by L. Hunter.....

**Warning:** 1) This CE Approval certificate is only valid when used in conjunction with an Article 11 Quality Control System in accordance with the PPE Directive 89/686/EC.

## Appendix 1 – Eyebolt Codes and Reference Numbers

Page 1 of 2

This certificate is the property of the National Engineering Laboratory and may not be reproduced other than in full except with the prior written approval of the issuing laboratory.

PPE/CE Approval cert\_Issue 3.0

## **Eyebolts**

### **100 mm shank length**

Eyebolt supplied in galvanised finish

5845-100G or (CSS12x100G if embossed Centurian)

Eyebolt supplied galvanised with brown plastic coating

5845-100B or (CSS12x100B if embossed Centurian)

Eyebolt supplied in stainless steel finish

5845-100S or (CSS12x100S if embossed Centurian)

Eyebolt supplied stainless steel with white plastic coating

5845-100W or (CSS12x100W if embossed Centurian)

### **152 mm shank length**

Eyebolt supplied in galvanised finish

5845-152G or (CSS12x152G if embossed Centurian)

Eyebolt supplied galvanised with brown plastic coating

5845-152B or (CSS12x152B if embossed Centurian)

Eyebolt supplied in stainless steel finish

5845-152S or (CSS12x152S if embossed Centurian)

Eyebolt supplied stainless steel with white plastic coating

5845-152W or (CSS12x152W if embossed Centurian)

### **204 mm shank length**

Eyebolt supplied in galvanised finish

5845-204G or (CSS12x204G if embossed Centurian)

Eyebolt supplied galvanised with brown plastic coating

5845-204B or (CSS12x204B if embossed Centurian)

Eyebolt supplied in stainless steel finish

5845-204S or (CSS12x204S if embossed Centurian)

Eyebolt supplied stainless steel with white plastic coating

5845-204W or (CSS12x204W if embossed Centurian)

## **Knurled Threaded Inserts**

M12 x 4 " Mild steel insert - KNURLM12MS

M12 x 4 " Stainless steel insert - KNURLM12SS

M12 x 76 Mild steel insert - KNURL3"MS

M12 x 76 Stainless steel insert - KNURL3"SS

M12 x 120 Mild steel insert - KNURL5"MS

M12 x 120 Stainless steel insert - KNURL5"SS

M12 x 152 Mild steel insert - KNURL6"MS

M12 x 152 Stainless steel insert - KNURL6"SS

**Adhesive** – M16 resin anchor capsule - RESIN16

**\*\*\*\*End of Certificate\*\*\*\***