

CE APPROVAL CERTIFICATE

Issued by : TUV NEL Ltd.

EC Notified Body No. 0320

Project No. PPE800000

NEL I.D.

Certificate No. BSEN795/08/010

Date of Issue 18 May 2008



NEL
East Kilbride, Glasgow,
G75 0QF, UK.

Tel No. 01355 220222
Fax No. 01355 272999

Customer Kee Safety Ltd.

Customer address Unit A2 Cradley Business Park, Overend Road, Cradley Heath, West Midlands, B64 7DW, UK.

Project No. PPE800000 **NEL Test Mark** MMMX-13 & 14

Product Received 26 July 1994 **Product Tested** 26 July 1994

Product Class A1 Structural Anchor

Model Anchorage device for use as a 'Through-type' anchorage in solid or cavity walls consisting of M12 threaded shank eyebolts supplied in 3 shank lengths i.e. 100, 152 and 204 mm and manufactured in hot galvanised steel or stainless steel and specifically designed as Class A1 EN795 anchorage device for use only on brick, stone or concrete.

Parameters See 'Appendix 1 – Eyebolt Codes and Reference Numbers' overleaf.

Category of PPE III

Method of Test Tests were carried out to the appropriate clauses of BSEN795 : 1994.

Remarks The above mentioned product fulfils the essential health and safety requirements of directive 89/686/EEC and its amendments.

Distribution
Kee Safety Ltd: 1 Copy
NEL : 2 Copies

Approved By D. Hare.....

Checked by L. Hunter.....

Warning: 1) This CE Approval certificate is only valid when used in conjunction with an Article 11 Quality Control System in accordance with the PPE Directive 89/686/EC.

Appendix 1 – Eyebolt Codes and Reference Numbers

Eyebolts

100 mm shank length

Eyebolt supplied in galvanised finish
5845-100G or (CSS12x100G if embossed
Centuryan)

Eyebolt supplied galvanised with brown plastic
coating
5845-100B or (CSS12x100B if embossed
Centuryan)

Eyebolt supplied in stainless steel finish
5845-100S or (CSS12x100S if embossed
Centuryan)

Eyebolt supplied stainless steel with white
plastic coating
5845-100W or (CSS12x100W if embossed
Centuryan)

152 mm shank length

Eyebolt supplied in galvanised finish
5845-152G or (CSS12x152G if embossed
Centuryan)

Eyebolt supplied galvanised with brown plastic
coating
5845-152B or (CSS12x152B if embossed
Centuryan)

Eyebolt supplied in stainless steel finish
5845-152S or (CSS12x152S if embossed
Centuryan)

Eyebolt supplied stainless steel with white
plastic coating
5845-152W or (CSS12x152W if embossed
Centuryan)

204 mm shank length

Eyebolt supplied in galvanised finish
5845-204G or (CSS12x204G if embossed
Centuryan)

Eyebolt supplied galvanised with brown plastic
coating
5845-204B or (CSS12x204B if embossed
Centuryan)

Eyebolt supplied in stainless steel finish
5845-204S or (CSS12x204S if embossed
Centuryan)

Eyebolt supplied stainless steel with white
plastic coating
5845-204W or (CSS12x204W if embossed
Centuryan)

Connectors

75 mm overall length coupler (galvanised steel)	- COUP12x3G
75 mm overall length coupler (stainless steel)	- COUP12x3SS
102 mm overall length coupler (galvanised steel)	- COUP12x4G
102 mm overall length coupler (stainless steel)	- COUP12x4SS

Backplates

Circular backplate (galvanised steel)	BPLATEGAL
Circular backplate (stainless steel)	- BPLATESS
Square backplate (galvanised steel)	- BPLATESQG
Square backplate (stainless steel)	- BPLATESQSS

Extension Rods

18" length of M12 spun/galvanised HTS all-thread	- THD12X18G
1 m length of M12 316 grade stainless steel all-thread	- THD12X1MSS

Nuts

M12 BZP Nyloc Nut	- NYLOCM12ZP
M12 316 grade stainless steel Nyloc nut	- MYLOCM12SS

****End of Certificate****